

Preparation Date: April 9, 2015

Revision Date: April 9, 2015

Version: 1

1. PRODUCT AND COMPANY IDENTIFICATION

| | |
|--|--|
| Product Name | Arisfor [®] Patch Kit – Cementitious Powder Component |
| Recommended Uses | Concrete damp-proofing coating |
| Restrictions on Use | No data |
| Supplier of the Safety Data Sheet including Address | Arisfor, LLC 100 Forta Drive Grove City, PA 16127 |
| Company Number | Phone: 724-264-1050 Fax: 724-458-8331 |
| Emergency Phone: | 724-264-1050 |

2. HAZARDS IDENTIFICATION

Emergency Overview

| | |
|---------------------------|--|
| OSHA Hazards | Harmful if swallowed. Causes severe skin burns and eye damage. Harmful if inhaled. Suspected of causing cancer by inhalation of respirable crystalline silica. Causes damage to Lungs through prolonged or repeated exposure by inhalation. |
| Target Organs | Lungs |
| GHS Classification | Acute Toxicity Oral – Category 4 Carcinogenicity – Category 2 Eye damage/eye irritation – Category 1 Skin sensitization – Category 1 Skin irritation – Category 1 Specific target organ toxicity – repeated exposure – Category 2, Respiratory System |

Label Elements (including precautionary statements)

Pictograms:



Signal word – Danger

Hazard Statements

| | |
|-------------|---|
| H302 | Harmful if swallowed. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H335 | May cause respiratory irritation. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure if inhaled. |

Precautionary Statements – Prevention

- P260** Do not breathe dust/fume/gas/mist/vapors/spray.
- P264** Wash hands and skin thoroughly after handling.
- P270** Do not eat, drink or smoke when using this product.
- P271** Use only outdoors or in a well-ventilated area.
- P272** Contaminated work clothing should not be allowed out of the workplace.
- P280** Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – Response

- P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P301+P330+P331** IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P310** Immediately call a POISON CENTER/doctor.
- P303+P313+P310** IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with plenty of water or shower. Immediately call a POISON CENTER/doctor.
- P363** Wash contaminated clothing before reuse.
- P333+P313** If skin irritation or rash occurs: Get medical advice or attention.
- P304+P340+P312** IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
- P308+P313** If exposed or concerned: Get medical advice/attention.
- P314** Repeated Exposure: Get medical advice/attention if you feel unwell.

Precautionary Statements – Storage

- P403+P233** Store in a well-ventilated place. Keep container tightly closed.

Precautionary Statements – Disposal

- P501** Dispose of contents/container in accordance with local/regional/national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Component | CAS# | % by Weight |
|--|---------------------------------------|-------------|
| Cement | 65997-15-1 | 20-30% |
| Crystalline Silica in the form of Quartz | 14808-60-7 | 60-70% |
| Calcium Magnesium Hydroxide | 39445-23-3 | 1-5% |
| Additives | Proprietary | ≤0.2% |
| Various Pigments Including: Titanium Dioxide Iron Oxide Blends | 13463-67-7 Various (Non-Hazardous) | 0.1-5% |

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels. Where a range is displayed, the exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

| | |
|-----------------------|---|
| General Advice | Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. |
| Inhalation | If breathed in, move person into fresh air and keep comfortable for breathing. Consult a physician. |
| Eye Contact | Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Consult a physician. |
| Ingestion | Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. |
| Skin Contact | Remove contaminated clothing. Wash off with soap and plenty of water. Consult a physician. |

5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable Extinguishing Media | Material is Non-combustible. Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide for surrounding fire. |
| Specific Hazards Arising from the Chemical | Avoid breathing dust. Wet cement is caustic. |
| Hazardous Combustion Products | Calcium Oxide, Sulfur Dioxide |
| Protective Equipment and Precautions for Firefighters | Wear self-contained breathing apparatus and full protective gear for firefighting. |
| Further Information | See Section 7 for safe handling and storage. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| Personal Precautions | Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. |
| Environmental Precautions | Prevent further leakage or spillage if safe to do so. Do not let product enter drains. |
| Methods and Material for Containment and Cleaning Up | Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). |

7. HANDLING AND STORAGE

| | |
|---|---|
| Precautions for Safe Handling | Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. |
| Conditions for Safe Storage, including any incompatibilities | General information: Keep bagged material dry until used. Stack bagged material in a secure manner to prevent falling. Bagged material is heavy and poses risks such as sprains and strains to the back, arms, shoulders and legs during lifting and mixing. Handle with care and use appropriate control measures. Incompatibilities: Water will cause product to solidify. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component Exposure Limits Cement CAS#: 65997-15-1 OSHA 15 mg/m³ T (Total) / 5 mg/m³ R (Respirable) Silica, Quartz CAS#: 14808-60-7 OSHA TWA 10 mg/m³, ACGIH TWA 0.025 mg/m³
Calcium Magnesium Hydroxide Hydrated CAS#: 39445-23-3 OSHA TLV 5 mg/m³.

Appropriate Engineering Controls **Local Ventilation:** Recommended
General Ventilation: Recommended

Individual Protection Measures, such as Personal Protective Equipment **Eye/Face Protection:** Use proper protection – Safety Glasses as a minimum.
Skin and Body Protection: Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.

Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided, or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State

| | |
|-----------------------|--|
| Appearance | Solid Powder |
| Color | Various Colors, Including White & Gray |
| Odor | Mild |
| Odor Threshold | No data |

Properties

| | |
|----------------------------------|---------------|
| Vapor Pressure | Not available |
| Vapor Density | Not available |
| Relative Density | Not available |
| pH (in water) | 12-13 |
| Melting/Freezing Point | Not relevant |
| Solubility | Not available |
| Evaporation Rate | Not available |
| Flash Point | Not relevant |
| Flammability Limits | Not available |
| Flammability (Solid, Gas) | Not relevant |

| | |
|---|---------------|
| Autoignition Temperature | Not available |
| Initial Boiling Point/ Boiling Range | Not available |
| Decomposition Temperature | Not available |
| Viscosity | Not available |
| Specific Gravity | Not available |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical Stability | Stable. |
| Possibility of Hazardous Reactions | Hazardous polymerization will not occur. |
| Conditions to Avoid | Keep dry until use. Avoid contact with incompatible materials. |
| Incompatible Materials | Wet cement is alkaline and is incompatible with acids, ammonium salts and aluminum metal. Cement dissolves in hydrofluoric acid, producing corrosive silicon tetrafluoride gas. Cement reacts with water to form silicates and calcium hydroxide. Silicates react with powerful oxidizers such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride. |
| Hazardous Decomposition Products | None known. |

11. TOXICOLOGICAL INFORMATION

| | |
|---|---|
| Likely Routs of Exposure | Inhalation, Skin contact, Eye contact, Ingestion. |
| Symptoms of Exposure | Inhalation: May cause respiratory irritation. Skin: Causes severe skin burns. May cause allergic skin reaction. Eyes: Causes serious eye damage. Ingestion: Irritation of the digestive system may occur if large amounts are swallowed. |
| Numerical Measures of Toxicity | Acute Toxicity Value: Silica-LD50 oral rat 22,500 mg/kg. |
| Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure | <p>Dermatitis: Irritant Dermatitis is caused by physical properties of cement including alkalinity and abrasion. Allergic Dermatitis is caused by sensitization to hexavalent chromium (Chromate) present in cement. The reaction can range from a mild rash to severe skin ulcers. Persons already sensitized may react to the first contact with cement. Others may develop allergic dermatitis after years of repeated contact with cement.</p> <p>Carcinogenicity: IARC: 1-Group 1: Carcinogenic to humans (Quartz) ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. NTP: Carcinogenic to humans (Quartz) OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.</p> <p>Specific target organ toxicity: Single exposure – No data available. Specific target organ toxicity: Repeated exposure – Category 2, Respiratory</p> |

System.

Silicosis: Silicosis is caused by the inhalation and retention of respirable crystalline silica dust.

Simple Chronic Silicosis - results from long-term exposure (more than 20 years) to low amounts of respirable crystalline silica. Nodules of chronic inflammation and scarring provoked by the respirable crystalline silica form in the lungs and chest lymph nodes. This disease may feature breathlessness and may resemble chronic obstructive pulmonary disease (COPD).

Accelerated Silicosis – occurs after exposure to larger amounts of respirable crystalline silica over a shorter period of time (5-15 years). Inflammation, scarring, and symptoms progress faster in accelerated silicosis than in simple silicosis.

Acute Silicosis – results from short-term exposure to very large amounts of respirable crystalline silica. The lungs become very inflamed and may fill with fluid, causing severe shortness of breath and low blood oxygen levels.

Pre-Existing Conditions: Cement dust is irritating to the nose, throat and respiratory tract causing coughing and sneezing. Pre-existing upper respiratory and lung diseases including asthma and bronchitis may be aggravated.

12. ECOLOGICAL INFORMATION

| | |
|--------------------------------------|--|
| Ecotoxicity | Not expected to be hazardous to the environment. |
| Persistence and Degradability | No data available. |
| Bioaccumulation | No data available. |
| Mobility | No data available. |
| Other Adverse Effects | No data available. |

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

| | |
|-------------------------------|---|
| Disposal of Wastes | This product is not expected to be a hazardous waste under RCRA. Place spilled material into a container. Scrape wet material and place in container. Allow material to dry or solidify before disposal. Dispose of according to Federal, State, Provincial and Local regulations.. |
| Contaminated Packaging | Dispose of as unused material. |

14. TRANSPORT INFORMATION

| | |
|-------------------------|-------------------------|
| DOT | Not a dangerous good. |
| IATA | Not a dangerous good. |
| IMDG | Not a dangerous good. |
| Marine Pollutant | Not a marine pollutant. |

15. REGULATORY INFORMATION

International Inventories

TSCA All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

U.S. Federal Regulations

SARA 302 None known.

SARA 311/312 Hazard Categories Acute health hazard, Chronic health hazard.

SARA 313 Hazard Categories None known.

CWA (Clean Water Act) None known.

Supplemental State Compliance Information

California Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.
Quartz CAS#:14808-60-7
Hexavalent Chromium Compounds.

| | | |
|---------------------------------|------------|----------------|
| New Jersey Right To Know | CAS Number | Component Name |
| | 14808-60-7 | Quartz |

| | | |
|-----------------------------------|------------|----------------|
| Pennsylvania Right To Know | CAS Number | Component Name |
| | 14808-60-7 | Quartz |

| | | |
|------------------------------------|------------|----------------|
| Massachusetts Right To Know | CAS Number | Component Name |
| | 14808-60-7 | Quartz |

U.S. EPA Label Information: No data.

Canada

WHMIS Classification Class D2B (Toxic) & Class E (Corrosive)

Symbol Stylized T, Corrosive



16. OTHER INFORMATION

HMIS Classification

Health Hazard 2

Flammability 0

Physical Hazard 0

NFPA Rating

Health Hazard 2

Fire 0

Reactivity Hazard 0

Preparation Date: April 9, 2015

Revision Date: April 9, 2015

Version: 1

1. PRODUCT AND COMPANY IDENTIFICATION

| | |
|--|---|
| Product Name | Arisfor [®] Patch Kit – Liquid Bond Component |
| Recommended Uses | High solids acrylic latex bonding agent and admixture |
| Restrictions on Use | No data |
| Supplier of the Safety Data Sheet including Address | Arisfor, LLC 100 Forta Drive Grove City, PA 16127 |
| Company Number | Phone: 724-264-1050 Fax: 724-458-8331 |
| Emergency Phone: | 724-264-1050 |

2. HAZARDS IDENTIFICATION

Emergency Overview

OSHA Hazards Causes eye irritation, may be harmful if swallowed, may cause an allergic skin reaction, may cause skin irritation.

GHS Classification Eye damage/irritation – Category 2B
Acute toxicity, Oral – Category 5
Sensitization, Skin – Category 1A

Label Elements, including precautionary statements

Pictogram –



Signal word – Warning

Hazard Statements

H303 May be harmful if swallowed.
H320 Causes eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.

Precautionary Statements – Prevention

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 Wash hands and skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – Response

| | |
|-----------------------|--|
| P312 | Call a POISON CENTER/doctor if swallowed and you feel unwell. |
| P304+P340+P312 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337+P313 | If eye irritation persists: Get medical advice or attention. |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice or attention. |
| P362+P364 | Take off contaminated clothing and wash it before reuse. |

Precautionary Statements – Storage

| | |
|-------------|------------------|
| P405 | Store locked up. |
|-------------|------------------|

Precautionary Statements – Disposal

| | |
|-------------|---|
| P501 | Dispose of contents/container in accordance with local/regional/national regulations. |
|-------------|---|

Hazards not otherwise classified: May cause skin irritation

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Name | CAS# | % by Weight |
|---------------------------------------|---------------|-------------|
| Water | 7732-18-5 | 70-75% |
| Latex Resin – Non-Hazardous | Not available | 20-25% |
| S-Triazine-1,3,5(2H,4H,6H)-Triethanol | 4719-04-4 | ≤0.3% |
| Surfactant Blend | Proprietary | ≤0.2% |

Ingredients not listed on this safety data sheet are considered to be non-hazardous according to OSHA 1910.1200 or are not present above their cutoff levels. Where a range is displayed, the exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

| | |
|-----------------------|---|
| General Advice | Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. |
| Inhalation | IF INHALED: Call a POISON CENTER/doctor if you feel unwell. |
| Eye Contact | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention. |
| Ingestion | IF SWALLOWED: Not expected to be harmful under normal conditions of use. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Call a POISON CENTER/doctor if you feel unwell. |
| Skin Contact | Wash off with plenty of soap and water. If skin irritation or rash occurs: Get medical advice or attention. |

5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Suitable Extinguishing Media | Material is not combustible. Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide for the surrounding fire. |
| Specific Hazards Arising from the Chemical | No specific data available. |
| Hazardous Combustion Products | No specific data available. |
| Protective Equipment and Precautions for Firefighters | Wear self-contained breathing apparatus and full protective gear for firefighting. |
| Further Information | See Section 7 for safe handling and storage. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|--|--|
| Personal Precautions, Protective Equipment and Emergency Procedures | In case of spill wear appropriate personal protective equipment during any cleanup and response activities. Avoid skin contact and inhalation. |
| Environmental Precautions | Prevent further leakage or spillage if safe to do so. Do not let product enter drains. |
| Methods and Material for Containment and Cleaning Up | Dike and contain spill with inert absorbent materials. Soak up with inert material and keep in suitable, closed containers for disposal. Dispose of in accordance with specified local/regional/national/international regulations for disposal. |

7. HANDLING AND STORAGE

| | |
|---|---|
| Precautions for Safe Handling | Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. |
| Conditions for Safe Storage, Including any Incompatibilities | <p>General information: Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep away from heat. Keep from freezing. Store product above 50 degrees F/10 degrees C and below 95 degrees F/35 degrees C.</p> <p>Safe Storage: No additional data.</p> <p>Incompatibilities: None known.</p> |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

| | |
|--|--|
| Component Exposure Limits | No data available. |
| Appropriate Engineering Controls | <p>Local Ventilation: Recommended</p> <p>General Ventilation: Recommended</p> |
| Individual Protection Measures, such as Personal Protective Equipment | <p>Eye/Face Protection: Use proper protection – Safety Glasses as a minimum.</p> <p>Skin and Body Protection: Wash at mealtime and end of shift. Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc.). Use chemical protective gloves as a minimum and wash skin promptly upon any skin contact.</p> <p>Respiratory Protection: Use respiratory protection unless adequate local exhaust ventilation is provided, or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.</p> |

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before & after breaks and work day.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State

| | |
|-----------------------|---------------------|
| Appearance | Liquid |
| Color | White (dries clear) |
| Odor | Mild |
| Odor Threshold | No data |

Properties

| | | |
|---|----------------|------------------------------|
| Vapor Pressure | Not available | |
| Vapor Density | Not available | |
| Relative Density | Not available | |
| pH | 9 | |
| Melting/Freezing Point | 32°F (0°C) | |
| Solubility | Not available | |
| Evaporation Rate | Not available | |
| Flash Point | >212°F (100°C) | Closed cup method |
| Flammability Limits | Not relevant | |
| Flammability (Solid, Gas) | Not relevant | |
| Autoignition Temperature | Not available | |
| Initial Boiling Point/ Boiling Range | >212°F (100°C) | |
| Decomposition Temperature | Not available | |
| Viscosity | Not available | |
| Specific Gravity | 1.03 | Density: 8.61 lb/gal +/-0.02 |

10. STABILITY AND REACTIVITY

| | |
|---|--|
| Chemical Stability | Stable |
| Possibility of Hazardous Reactions | None known. |
| Conditions to Avoid | Keep from freezing. |
| Incompatible Materials | None known. |
| Hazardous Decomposition Products | Oxides of carbon, sulphur, and nitrogen. |

11. TOXICOLOGICAL INFORMATION

| | |
|---|--|
| Likely Routs of Exposure | Skin contact, eye contact. (Ingestion is not a likely route of exposure under normal conditions of use.) |
| Symptoms of Exposure | Allergic skin reaction, skin and eye irritation, stomach or intestinal upset. |
| Numerical Measures of Toxicity | No data available. |
| Delayed and Immediate Effects as well as Chronic Effects from Short and Long-Term Exposure | May be harmful if swallowed. May cause allergic skin reaction, skin and eye irritation. Carcinogenicity: No ingredient has been characterized as a potential carcinogen by either IARC, NTP or OSHA. |

12. ECOLOGICAL INFORMATION

| | |
|--------------------------------------|---|
| Ecotoxicity | No known significant effects or critical hazards. |
| Persistence and Degradability | No data available. |
| Bioaccumulation | No data available. |
| Mobility | No data available. |
| Other Adverse Effects | No know significant effects or critical hazards. |

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

| | |
|-------------------------------|---|
| Disposal of Wastes | This product is not a hazardous waste under RCRA. Dispose of in conformance with all federal, state, and local regulations. |
| Contaminated Packaging | Dispose of as unused material. |

14. TRANSPORT INFORMATION

| | |
|--------------------------|--------------------------------------|
| DOT Requirements | Not a DOT controlled material (USA). |
| IMDG Requirements | Not an IMDG controlled material. |
| IATA Requirements | Not an IATA controlled material. |
| Marine Pollutant | Not a marine pollutant. |

15. REGULATORY INFORMATION

International Inventories

TSCA All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

U.S. Federal Regulations

SARA 302 None known.

**SARA 311/312
Hazard Categories** Acute health hazard.

**SARA 313
Hazard Categories** None known.

**CWA
(Clean Water Act)** None known.

Supplemental State Compliance Information

California This product does not contain any chemical(s) listed by the State of California under the Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

U.S. EPA Label Information: No data.

Canada

**WHMIS
Classification** Class D2B (Toxic)

Symbol Stylized T



16. OTHER INFORMATION

HMIS Classification

Health Hazard 1

Flammability 0

Physical Hazard 0

NFPA Rating

Health Hazard 1

Fire 0

Reactivity Hazard 0