

Preparation Date: --

Revision Date: December 5, 2018

Version: 1.3

1. PRODUCT AND COMPANY IDENTIFICATION

| | |
|---|---|
| Product Identifier | CPMC-LV-003 |
| Other Product Names | Arisfor [®] Multi-Surface Waterproofer (Low VOC Formulations) |
| Brand | Arisfor, LLC |
| Supplier | Arisfor, LLC 100 Forta Drive Grove City, PA 16127 |
| Recommended Uses / Restrictions on Use | New and/or resurfaced masonry & concrete |
| Company Number | Phone: 724-264-1050 |
| Emergency Phone: CHEMTEL | Domestic: 1-800-255-3924 International: +1-813-248-0585 |

2. HAZARDS IDENTIFICATION

Emergency Overview

Highly flammable liquid and vapor. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

For Exterior Use Only. Use only with adequate ventilation. To avoid overexposure; if treating enclosed exterior rooms or porches, open windows and doors or use other means to ensure fresh air during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Wear protective gloves/ protective clothing. Avoid contact with eyes and skin. Cause eye, skin and respiratory tract irritation. Cause damage to organs. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

OSHA Hazards Flammable Liquid, Target Organ Effect, Toxic by Inhalation, Toxic by Ingestion, Toxic by Skin Absorption.



Target Organs Eyes, Kidney, Liver, Heart, Central Nervous System

GHS Classification Flammable Liquids – Category 2
Acute Toxicity, Oral – Category 3
Acute Toxicity, Inhalation – Category 3
Acute Toxicity, Dermal – Category 3

GHS Label Elements (including precautionary statements) Signal word – Danger

Hazard Statements

| | |
|------|------------------------------------|
| H225 | Highly flammable liquid and vapor. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H370 | Causes damage to organs. |

Precautionary Statements – Prevention

| | |
|------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. No smoking. |
| P233 | Keep container tightly closed. |
| P235 | Keep cool. |
| P240 | Ground/bond container and receiving equipment. |
| P241 | Use explosion proof electrical/ventilating/lighting/equipment. |
| P242 | Use only non-sparking tools. |
| P243 | Take precautionary measures against static discharge. |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray. |
| P264 | Wash skin thoroughly after handling. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P280 | Wear protective gloves/protective clothing. |

Precautionary Statements – Response

| | |
|----------------|---|
| P301+P310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340+P312 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P307+P311 | IF exposed: Call a POISON CENTER or doctor/physician. |
| P337+P313 | If eye irritation persists: Get medical advice or attention. |
| P370+P378 | In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. |

Precautionary Statements – Storage

| | |
|------|-----------------------------------|
| P403 | Store in a well-ventilated place. |
| P405 | Store locked up. |

Precautionary Statements – Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional Precautionary Statements

Wash exposed areas thoroughly after handling. Use only outdoors or in a well-ventilated area. Do not eat, drink, or smoke while using this product. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Take off immediately all contaminated clothing and wash it before reuse. Rinse mouth. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Specific treatment (see FIRST AID MEASURES on the SDS). In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide to extinguish. Store in a well-ventilated place. Keep cool. Keep container tightly closed. Keep locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

HMIS Classification

| | |
|------------------------------|---|
| Health Hazard | 2 |
| Chronic Health Hazard | * |
| Flammability | 3 |
| Physical Hazard | 0 |

NFPA Rating

| | |
|--------------------------|---|
| Health Hazard | 2 |
| Fire | 3 |
| Reactivity Hazard | 0 |

Hazards Not Otherwise Classified

May cause corneal damage following prolonged contact with the eye(s).

Percentage of Ingredients with Unknown Toxicity

Total percentage: ≤50%

Potential Health Effects

| | |
|-------------------|---|
| Inhalation | Toxic if inhaled. Causes respiratory tract irritation. |
| Skin | Toxic if absorbed through skin. Causes skin irritation. |
| Eyes | Causes eye irritation. |
| Ingestion | Toxic if swallowed. |

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Component | Classification | Concentration |
|---|---|---------------|
| Ethanol | | |
| CAS-No. 64-17-5 EC-No. 200-578-6 Index-No. 603-002-00-5 | Flam. Liq. 2; Eye Irrit. 2A; Carc. 1A | <1% |
| Acetone | | |
| CAS-No. 67-64-1 EC-No. 200-662-2 Index-No. 606-001-00-8 | Flam. Liq. 2; Acute Tox. 3; Skin Irrit. 2; Eye Irrit. 2 | 40 – 65% |
| Proprietary Substance(s) | | |
| N/A | N/A | 5 – 50% |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. The specific chemical identities and percentages of concentration have been withheld as trade secrets.

4. FIRST AID MEASURES

| | |
|--|---|
| General Advice | Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area. |
| Ingestion | IF SWALLOWED: Call hospital emergency room, or physician immediately. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician. |
| Inhalation | IF INHALED: If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician. |
| Skin Contact | Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician. |
| Eye Contact | Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. |
| Most Important Symptoms (Acute and Delayed) | Upon excessive exposure (inhalation, dermal contact, contact with eyes, ingestion), acute/delayed symptoms may include but are not limited to dizziness, nausea, fatigue, blurred vision, loss of motor skills, confusion, impaired judgement, and other common symptoms of inebriation typically associated with exposure to ethyl alcohol. Any individual exhibiting signs of these symptoms should seek immediate medical attention in accordance with the guidelines presented in Section 2 (HAZARDS IDENTIFICATION) and Section 4 (FIRST AID MEASURES) of this document. |
| Immediate Medical Attention Required | IF SWALLOWED: Immediately call a doctor/ physician. IF exposed: Call a doctor/ physician. Refer to Section 2 (HAZARDS IDENTIFICATION) and Section 4 (FIRST AID MEASURES) of this document for additional information. |

5. FIRE-FIGHTING MEASURES

| | |
|--|---|
| Conditions of Flammability | Flammable in the presence of a source of ignition when the temperature is above the flash point. Keep away from heat/sparks/open flame/hot surface. No smoking. |
| Suitable Extinguishing Media | Use water spray, alcohol-resistant foam, dry chemical, or carbon dioxide. |
| Special Protective Equipment for Firefighters | Wear self-contained breathing apparatus for fire-fighting if necessary. |
| Hazardous Combustion Products | Hazardous decomposition products formed under fire conditions. – Carbon oxides. |
| Further Information | Use water spray to cool unopened containers. |

6. ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| Personal Precautions | Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas. |
| Environmental Precautions | Prevent further leakage or spillage if safe to do so. Do not let product enter drains. |
| Methods and Material for Containment and Cleaning Up | Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). |

7. HANDLING AND STORAGE

| | |
|--------------------------------------|---|
| Precautions for Safe Handling | Avoid contact with skin and eyes. Avoid inhalation of vapor or mist. Use explosion-proof equipment. Keep away from sources of ignition – No smoking. Take measures to prevent the build-up of electrostatic charge. |
| Conditions for Safe Storage | Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. |

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Components with Workplace Control Parameters

| Components | CAS-No. | Value | Control Parameters | Basis |
|----------------|---|-------|---|---|
| Ethanol | 64-17-5 | TWA | 1000 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| Remarks | Upper Respiratory Tract irritation, Confirmed animal carcinogen with unknown relevance to humans. | | | |
| | | TWA | 1,000 ppm 1,900 mg/m ³ | USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000 |
| | | TWA | 1,000 ppm 1,900 mg/m ³ | USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminants. |
| | The value in mg/m ³ is approximate. | | | |
| | | TWA | 1,000ppm 1,900mg/m ³ | USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminants |
| | The value in mg/m ³ is approximate. | | | |
| | | TWA | 1,000ppm 1,900mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | | STEL | 1,000 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | | | Upper Respiratory Tract irritation, Confirmed animal carcinogen with unknown relevance to humans. | |
| Acetone | 67-64-1 | TWA | 500 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| Remarks | Central Nervous System impairment. Hematologic effects, Upper Respiratory Tract irritation, Eye irritation. Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen. | | | |
| | | TWA | 250 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Central Nervous System impairment, Upper Respiratory Tract irritation, Eye irritation. 2015 Adoption Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen. | | | |
| | | STEL | 750 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| | Central Nervous System impairment, Hematologic effects, Upper Respiratory Tract irritation, Eye irritation. Adopted values or notations enclosed are those for which changes are proposed in the NIC, See Notice of Intended Changes (NIC) Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen. | | | |
| | | STEL | 500 ppm | |
| | Central Nervous System impairment. Upper Respiratory Tract irritation. Eye irritation. 2015 Adoption Substances for which there is a Biological Exposure Index or Indices (see BEI® section). Not classifiable as a human carcinogen. | | | |
| | | TWA | 1,000ppm 2,400 mg/m ³ | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | The value in mg/m ³ is approximate. | | | |

| | | | | |
|---------------------------------|---|-----|----------------------------------|--|
| | | TWA | 250 ppm 590 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| Proprietary Substance(s) | | TWA | 10 ppm | USA. ACGIH Threshold Limit Values (TLV) |
| Remarks | Eye & Upper Respiratory Tract Irritation, Kidney Damage | | | |
| | | TWA | 10 ppm 85 mg/m ³ | USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000 |
| | | TWA | 100 ppm 850 mg/m ³ | USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants |
| | | TWA | 10 ppm 85 mg/m ³ | USA. NIOSH Recommended Exposure Limits |
| | The value in mg/m ³ is approximate. | | | |

Appropriate Engineering Controls

To eliminate or reduce exposure to potential chemical and/or physical hazards while using this material, do NOT use/handle/store/transport/dispose/transfer material in any other way other than as specified in either this document or the corresponding Technical Data Sheet for Arisfor® Multi-Surface Waterproof. Always use non-sparking materials when using/handling/storing/transporting/disposing/transferring material. Always store material in a tightly-sealed appropriate/approved storage vessel and properly stowed away in an approved fire-/flame-resistant storage area.

Personal Protective Equipment

Respiratory Protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand Protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye Protection

Face shield and safety glasses. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166 (EU).

Skin and Body Protection

Complete suit protecting against chemicals, flame retardant antistatic protective clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene Measures

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

| | |
|--------------|--------------------------|
| Form | Liquid |
| Color | Colorless/Color of stain |

Safety Data

| | |
|--|---------------------------------|
| VOC | 400 g/L |
| pH | 5-8 |
| Melting/Freezing Point | No data available. |
| Boiling Point | >55°C (131°F) |
| Flash Point | >12.5°C (9.5°F) |
| Ignition Temperature | No data available. |
| Decomposition Temperature | No data available. |
| Autoignition Temperature | No data available. |
| Lower Explosion Limit | No data available. |
| Upper Explosion Limit | No data available. |
| Vapor Pressure | No data available. |
| Density | 0.90 – 1.07 g/mL @ 25°C (77°F) |
| Viscosity | 0.97 – 1.20 mPa·s @ 25°C (77°F) |
| Water Solubility | No data available. |
| Partition Coefficient n-octanol/water | No data available. |
| Relative Water Density | No data available. |
| Odor | Pleasant |
| Odor Threshold | No data available. |
| Evaporation Rate | No data available. |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Chemical Stability | Stable under recommended storage conditions. |
| Reactivity | Flammable: May explode when exposed to flame. Stability: Stable material. Hazardous Polymerization: Will not occur. |
| Possibility of Hazardous Reactions | Vapors may form explosive mixture with air. |
| Conditions to Avoid | Heat, flames and sparks. Extremes of temperature and direct sunlight. |
| Materials to Avoid | Acid chlorides, Acid anhydrides, Oxidizing agents, Alkali metals, Reducing agents, Acids. |
| Hazardous Decomposition Products | Hazardous decomposition products formed under fire conditions – Carbon oxides. Other decomposition products – No data available. |

11. TOXICOLOGICAL INFORMATION

| | |
|--|--|
| Acute Toxicity Estimate (ATE) | ATE US (Oral): No data available. ATE US (Dermal): No data available. ATE US (Vapors): No data available. |
| Skin Corrosion/Irritation | Causes skin irritation. |
| Serious Eye Damage/Eye Irritation | Causes serious eye irritation. |
| Respiratory or Skin Sensitization | Not classified. |
| Germ Cell Mutagenicity | Genotoxicity in vitro - Ames test - S. typhimurium - with and without metabolic activation – negative. Genotoxicity in vitro - in vitro assay - fibroblast – negative. Mutation in mammalian somatic cells. Genotoxicity in vivo - mouse - male and female - Intraperitoneal – negative. In vivo studies have shown that repeated exposure to this material, even at otherwise toxic doses, does not cause any mutagenic events. No tumorigenic response to the chronic recurrent application of the material to the skin of mice was observed. |
| Carcinogenicity | Not classified. |
| Reproductive Toxicity | Not classified. |
| Teratogenicity | Not classified. |
| Specific Target Organ Toxicity - Single Exposure (Globally Harmonized System) | Not classified. |
| Specific Target Organ Toxicity - Repeated Exposure (Globally Harmonized System) | Not classified. |
| Aspiration Hazard | Not classified. |

| | |
|---------------------------------|---|
| Potential Health Effects | Inhalation: Toxic if inhaled. Causes respiratory tract irritation. Ingestion: Toxic if swallowed. Skin: Toxic if absorbed through skin. Causes skin irritation. Eyes: Causes eye irritation. |
|---------------------------------|---|

12. ECOLOGICAL INFORMATION

| | |
|--------------------------------------|--|
| Toxicity (Acetone) | Toxicity to fish: No data available. Toxicity to daphnia and other aquatic invertebrates: No data available. Toxicity to algae: No data available. |
| Persistence and Degradability | No data available. |
| Bioaccumulative Potential | Does not bioaccumulate. |
| Mobility in Soil | No data available. |
| Other Adverse Effects | Effect on Ozone Layer: No data available. Effect on Global Warming: No data available. Additional Ecological Information: Avoid release to the environment. |

13. DISPOSAL CONSIDERATIONS

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

| | |
|-------------------------------|-------------------------------|
| Contaminated Packaging | Dispose of as unused product. |
|-------------------------------|-------------------------------|

14. TRANSPORT INFORMATION

| | |
|-----------------|---|
| DOT (US) | UN Number: 1993 Class: 3 Packing Group: II Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (ACETONE), 3, II |
|-----------------|---|

15. REGULATORY INFORMATION

| | |
|--|---|
| United States Inventory (TSCA 8b) | All components are listed or exempted. |
| OSHA Hazards | Flammable and Combustible liquid, Target Organ Effect, Toxic by inhalation, Toxic by ingestion, Toxic by skin absorption. |
| SARA 302 Components | No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. |
| SARA 311/312 Hazards | Fire hazard, Acute health hazard, Chronic health hazard. |
| California Prop. 65 Components | This product contains a chemical (Ethanol (64-17-5)) known to the State of California to cause cancer, birth defects, reproductive harm, or developmental toxicity. |

16. OTHER INFORMATION

Additional Information

Copyright 2018, Arisfor, LLC. License granted to make unlimited paper copies for internal use only. This material safety data sheet was last modified on 12/5/2018. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Arisfor, LLC. and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.arisfor.com for additional terms and conditions of sale.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by Arisfor, LLC, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.